B One







Specifications

WAN Interface	2x 10/100/1000 Ethernet	Power Input	DC 12V
LAN Interface	1x 10/100/1000M Ethernet	Power Consumption	24W (max.)
Wi-Fi Interface	Simultaneous Dual-Band (2.4GHz / 5GHz) Wi-Fi 6 4x4 MIMO	Dimensions	6.3 x 3.4 x 8.5 inches / 160 x 86 x 215 mm
	Wi-Fi WAN and/or AP	Weight	2.76 pounds / 1250 grams
SpeedFusion Features	Hot Failover ¹ , WAN Smoothing ¹ , Bandwidth Bonding ¹	Operating Temperature	32° - 113°F / 0° - 45°C
	J	Humidity	5% – 95% (non-condensing)
Number of SpeedFusion VPN Peers	2/5 ²	Certifications ³	CE, RoHS
Router Throughput	1Gbps	Package Content	1x B One
SpeedFusion Throughput (No Encryption)	400 Mbps	Warranty	1x 12V 2A Power Supply 1-Year Limited Warranty
SpeedFusion Throughput (256-bit AES)	200 Mbps		
Recommended Users	1-150		

Standard

AP Controller

Maximum Number of AP Supported

Specifications are subject to change without notice.

¹ Requires a PrimeCare subscription, complimentary for the first year. ² 5 SpeedFusion VPN Peers are enabled for PrimeCare models which requires a PrimeCare subscription, complimentary for the first year. ³ Certifications pending.

B One



Ordering Information

Product CodeRegionsB-ONE-T-PRMGlobal

Featured Add-on

Description
PrimeCare B (1-Year)
PrimeCare B (2-Year)
PrimeCare B (4-Year)
PrimeCare+ B (1-Year)
PrimeCare+ B (2-Year)
PrimeCare+ B (4-Year)